



Change for Life

Submittal Data :Cassette Units		GKH<12>BA-D3DNA2A/I	
Job Name :		Date :	
Engineer :		Submitted to :	
Location :		Submitted by :	
Tag # :		Schedule / Drawing # :	
For :	<input type="checkbox"/> Reference <input type="checkbox"/> Approval <input type="checkbox"/> Construction		

- GENERAL FEATURES**
- Quiet Operation -Multi-Speed Fan
 - 4-way Discharge Air
 - Internal Condensate Drain Pump
 - Swing Louver
 - Both Wireless & Wired Remote Controllers
 - Power Failure Recovery
 - Sentry Condensate Overflow Protection
 - Flare connection
 - Decorative Grille (Sold Separately)



Cooling		Air Flow	
Cooling Capacity	12,000 Btu/h	Air Flow Volume	353/0/0 CFM
Cooling Speed	845/700/600/515 r/min	Sound Pressure Level	//46.00 dB(A)
Recommended Power Cable(Core)	4	Sound Power Level	//56 dB(A)
Cross-sectional Area of Power Cable Conductor	AWG18 <0.82>		
		Electrical	
Heating		Power supply	230V-1Ph -60Hz
Heating Capacity	13,000 Btu/h	Fuse Current	/ A
		Fan Motor Power Output	11 W
		Number of fans	1 N
		Fan Type	Axial-flow
Set Temperature Range ° F			61 ~ 86

Physical & Piping			
Base Unit Dimension (WxDxH)	570x570x230 mm	Liquid Line connection	1/4 in
Net Weight	18 kg	Gas connection	3/8 in
Panel Net Weight	2.5 kg	Panel Dimension(LxWxH)	650 x650 x50 mm



1-833-666-GREE
www.greehvac.ca

Manufacturer has right to change the data without notice, please refer to the name plate of the unit.