



Change for Life

<b>Submittal Data :Cassette Units</b>		<b>GKH&lt;18&gt;BA-D3DNA2A/I</b>	
Job Name :		Date :	
Engineer :		Submitted to :	
Location :		Submitted by :	
Tag # :		Schedule / Drawing # :	
For :	<input type="checkbox"/> Reference	<input type="checkbox"/> Approval	<input type="checkbox"/> Construction

- GENERAL FEATURES**
- Quiet Operation -Multi-Speed Fan
  - 4-way Discharge Air
  - Internal Condensate Drain Pump
  - Swing Louver
  - Both Wireless & Wired Remote Controllers
  - Power Failure Recovery
  - Sentry Condensate Overflow Protection
  - Flare connection
  - Decorative Grille



Cooling		Air Flow	
Cooling Capacity	14,400 Btu/h	Air Flow Volume	353/0/0 CFM
Cooling Speed	845/700/600/515 r/min	Sound Pressure Level	//46.00 dB(A)
Recommended Power Cable(Core)	4	Sound Power Level	//56 dB(A)
Cross-sectional Area of Power Cable Conductor	AWG18 <0.82>		
		Electrical	
		Power supply	208V-1Ph -60Hz
<b>Heating</b>		Fuse Current	/ A
Heating Capacity	16,000 Btu/h	Fan Motor Power Output	11 W
		Number of fans	1 N
		Fan Type	Axial-flow
Set Temperature Range ° F		61 ~ 86	

Physical & Piping			
Base Unit Dimension (WxDxH)	570x570x230 mm	Liquid Line connection	1/4 in
Net Weight	18 kg	Gas connection	1/2 in
Panel Net Weight	2.5 kg	Panel Dimension(LxWxH)	650 x650 x50 mm



1-833-666-GREE  
[www.greehvac.ca](http://www.greehvac.ca)

Manufacturer has right to change the data without notice, please refer to the name plate of the unit.