

208~230V Heat Recovery

Model:
GMV-Q192WM/B-F(U)



+




Specifications	Unit	Parameter
Model	—	GMV-Q96WM/B-F(U) x 2
Performance		
Rated Cooling Capacity (*1)	kBtu/h	192
Rated Heating Capacity (*2)	kBtu/h	216
Power Input	Cooling(kw)	14.6
	Heating(kw)	15.7
Sound Pressure Level	dB(A)	63
Operating Temperature Range	Cooling (Outdoor) °C/°F	-5~52/23~125.6
	Heating (Outdoor) °C/°F	-20~24/-4~75
AHRI Ratings(Ducted /Non-Ducted)		
EER	W/W	10.60/10.60
IEER	—	21/20
COP	W/W	3.25/3.2
Electrical Data		
Power Supply	V/Ph/Hz	208/230/3/60
Maximum Overcurrent Protection (MOP)	A	45 + 45
Minimum Circuit Amps (MCA)	A	37 + 37
Fan		
Type x Quantity	—	Axial-flow x 4
Air Flow Volume	CFM	16480
Fan Motor Power Output	W	750 x 4
Max. External Static Pressure (ESP)	Pa/In.W.G	82/0.33
Compressor		
Compressor Type x Quantity	—	Inverter Scroll x 2
Compressor Refrigerant Oil Type	—	FVC68D or FV-68H
Compressor Refrigerant Oil Charge Volume	L/Gal	6.6/1.74 x 2
Refrigerant Piping		
Connection Pipe	High Pressure Gas(mm/inch)	Φ22.2/Φ7/8
	Low Pressure Gas(mm/inch)	Φ28.6/Φ1-1/8
	Liquid(mm/inch)	Φ12.7/Φ1/2
Max. Equivalent Connection Pipe Length (ODU to IDU)	m/ft	165/541
Refrigerant Charge	LBS	24.69 x 2
Refrigerant	—	R410A
Dimension/Weight		
Dimensions (H×W×D)	mm/inch	1605×1340×765 x 2 (52-3/4×30-1/8×63-1/4) x 2
Net Weight	kg/lbs	310/683 x 2
Other		
Indoor Unit	Total Capacity (%)	50%~135%
	Max Connectable Quantity	25
Certification	—	ETL/AHRI
Condenser Fin Color	—	Gold
Protection Devices	High Pressure	High pressure sensor, High pressure switch 601 psi (4.15 MPa)
	Inverter Circuit	Over-heat protection, Over-current protection
	Compressor	Discharge temp protection, Over-current protection

*1 Cooling | Indoor: 80°F (26.7°C) DB / 67°F (19°C) WB; Outdoor: 95°F (35°C) DB
*2 Heating | Indoor: 70°F (21.1°C) DB / Outdoor: 47°F (8.3°C) DB / 43°F (6°C) WB



Job Name:		Date:	
System Reference No.:			
Engineer Signature:			

Outline and Physical Dimensions of GMV-Q192WM/B-F(U)



Unit:mm(in.)

