



GREE				Multi-Roor	n Ductless systems
Submittal Data: GEH<0	9>AA-D3DNA1C/I	9,000 BT	U/H Mini Floor	Console Unit	
Job Name		Location		Date	
Purchaser		Enginee	r		
Submitted To		For	☐ Reference	☐ Approval	☐ Construction
Unit Designation		Schedule	e No.		
GENERAL FEATURES					
-Quiet Operation -Multi-Speed Fan -Swing Louvers -Wireless Remote Controller -Remote Control Lockout - 10 yr. Unlimited Parts Warranty					27
System Rati Cooling*				al Specificatio	
Rated Capacity	8,874 BTU/H	Unit Dime	ensions (LxHxD)		27.5 x 24.0 x 8.5 -in 700 x 600 x 215-mm
Heating*					700 X 000 X 2 15-111111
Rated Capacity	9,556 BTU/H	Weight (	Net/Shipping)		33/40 LBS
	·		11 0,		
Sound Pressure (Hi/Lo)**		Drain Size	(OD)		0.67-in
Cooling	40/25 dbA				17-mm
Heating	40/25 dbA				
Air Flow (max)					
Indoor Fan	294 CFM				
maoor ran	204 OI WI				
51	Refrigerant Piping Data				
Electrical Ra	tings		Retrige	erant Piping Da	ita
Fan Motor		Refrigera	nt Type		R410A
Output Power	30 W	15190.0	- · / P *		
FLA	0.36 A	Gas Pipe	Size (OD)		3/8-in
Power Supply		Liquid Pip	e Size (OD)		1/4-in
Normal Operational Voltage	208/230 V, 1 Phase, 60 Hz				
Voltage Range	187 - 253 V	Connection	on Method		Flared
MCA	1.0 A	1			
Interconnecting Cable Wire Size	14-4 AWG	* Took constit	iono ara bassal s.: ^	UDI 240/040	
			ions are based on A		350
**Sound Power ratings are per AHRI 270 and AHRI 350					
Non exame deplating refriguerant		ERTIFIED 194 www.ahridirectory.org			(FID)

## **DIMENSIONAL SPECIFICATIONS**


## GEH<09>AA-D3DNA1C/I



Front



Back



Dimensions

(mm) (inches)

Α	В	С	Н	
700	215	200	600	
27.6	8.5	7.875	23.6	

Note: Size refrigerant lines based on evaporator port sizes.

## **MINIMUM & MAXIMUM CLEARANCES**



## Notes

- 1. Recommended Interconnecting Cable Type Stranded Bare Copper Conductors THHN 600V Unshielded Wire
- 2. Power wiring cable size must comply with applicable national and local codes.
- 3. Test conditions are based on AHRI 210/240.

